



US009638425B2

(12) **United States Patent**
Inada et al.

(10) **Patent No.:** **US 9,638,425 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **CARTRIDGE-TYPE GAS GRILL**

(56) **References Cited**

(71) Applicants: **Iwatani Corporation**, Osaka (JP);
Asahi Seisakusho Co., Ltd., Saitama (JP)

U.S. PATENT DOCUMENTS

3,538,907 A * 11/1970 Bowman A47J 37/0713
126/214 R
5,546,853 A * 8/1996 Heil A47J 37/0713
126/25 R

(72) Inventors: **Kenichiro Inada**, Osaka (JP); **Akio Wada**, Saitama (JP)

(Continued)

(73) Assignees: **Iwatani Corporation**, Osaka (JP);
Asahi Seisakusho Co., Ltd., Saitama (JP)

FOREIGN PATENT DOCUMENTS

JP H08-320122 A 12/1996
Primary Examiner — Avinash Savani
Assistant Examiner — Rabeeul Zuberi
(74) *Attorney, Agent, or Firm* — Osha Liang LLP

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 367 days.

(21) Appl. No.: **14/260,797**

(22) Filed: **Apr. 24, 2014**

(65) **Prior Publication Data**

US 2015/0075516 A1 Mar. 19, 2015

(30) **Foreign Application Priority Data**

Sep. 13, 2013 (JP) 2013-190102

(51) **Int. Cl.**

A47J 37/07 (2006.01)

F24C 3/12 (2006.01)

(52) **U.S. Cl.**

CPC **F24C 3/12** (2013.01); **A47J 37/0713** (2013.01); **A47J 2037/0777** (2013.01)

(58) **Field of Classification Search**

CPC **F24C 3/12**; **A47J 37/0713**
See application file for complete search history.

(57) **ABSTRACT**

A structure which performs safety operation with certainty when a gas container is replaced or when an abnormality occurs and is easy to be used is provided. A cartridge-type gas grill **11** having a plurality of systems includes two gas container accommodation sections **12**; two burners **13**; and gas flow paths for connecting the gas container accommodation sections **12** and the burners **13** in a one-to-one relationship. All the gas container accommodation sections **12** are each provided with a container attachment switch **19** for detecting that a gas container **15** is connected. Open/close valves **18**, provided in the gas flow paths, for adjusting a gas flow are each formed of an electromagnetic valve. Operation knobs **63** each for making an operation on the corresponding open/close valve **18** are each provided with an ignition switch **20**, which is turned ON when the corresponding open/close valve **18** is opened and is turned OFF when the corresponding open/close valve **18** is closed. The container attachment switches **19**, the open/close valves **18**, and the ignition switches **20** are electronically controlled. For an ignition process, the ignition switches are validated under the condition that all the container attachment switches **19** are ON. For a recovery process, all the ignition switches **19** need to be turned OFF.

4 Claims, 15 Drawing Sheets

